

Series	Coupling Description	Towing Eye Size	Application				
				DC-Value	V-Value	S-Value	
6434 6451	34mm pin	40mm	Emergency shunting only	-	-	-	Trailer load = 20 t Trailer load = 25 t
2020	40mm	40mm	On road	30 kN	18 kN	350 kg	30 kN
4040 G 135 4040 G 145 4040 G 150	40mm Standard	40mm	On road / off road	70 kN 92 kN 92 kN	28.2 / 25 kN 38 kN 40 kN	700 / 1000 kg 1000 kg 1000 kg	85 kN 100 kN 137 kN
4045 G 150	40mm	40mm	On road / off road Tankers	-	-	-	137 kN
5050 G 150	50mm Standard	50mm	On / off road	135 kN	75 / 63 kN	1000 / 2000 kg	200 kN
5051 B	50mm Heavy Duty	50mm	On road / off road Road trains and	135 kN	75 / 63 kN	1000 / 2000 kg	285 kN
65 G 150	76mm NATO Hook	76mm	On / off road	Trailer load 35t		1000 kg	140 kN

<b>Trailer Couplings</b> The strong connection							
Series	Coupling Description	Towing Eye Size	Application	DC-Value	V-Value	S-Value	D-Value
VBG 8500	50mm Rubber Buffered	50mm	On road / off road	-	-	-	190kN
VBG 590 VR-2	50mm Heavy Duty	50mm	On road / off road Road trains and Abnormals	140 / 130kN	90 / 63 kN	1000 / 2000 kg	285 kN
VBG 760	57mm Automatic Rubber Buffered	57mm	On road / off road	-	-	-	200kN
VBG 795 VR-2	57mm Heavy Duty	57mm	On road / off road Road trains and Abnormals	145 / 150 kN	95 / 75kN	1000 / 2000 kg	290kN

<b>RINGFEDER</b> The strong connection We care all the way		<b>FALKENROTH</b> a Mahindra Forgings Europe AG company		<b>Towing Eyes</b>			
Series	Towing Eye Description	DC-Value	V-Value	S-Value			
05.398.30.79.0	40mm weld-on	66 kN	20 kN	900 kg	125 kN		
05.398.30.80.0	40mm removable	74 kN	23 kN	1000 kg	125 kN		
05.398.02.27.0	50mm weld-on	-	-	-	314 kN		
05.398.81.11.0	50mm removable	90 kN	25 kN	1000 kg	190 kN		
RF14990683	50mm flange	135 kN	75 / 50 kN	1000 / 2500 kg	190 kN		
RF09994939	50mm - clamped	135 kN	75 / 63 kN	1000 / 2500 kg	320 kN		
VBG15016000	57mm removable	120 kN	40 kN	1000 kg	190 kN		
VBG15019000	57mm flange	145 / 150 kN	95 / 75 kN	1000 / 2000 kg	290 kN		
VBG17014400	76mm weld-on	-	-	-	190 kN		
VBG17017200	76mm removable	120 kN	40 kN	1000 kg	190 kN		
10.03.976196	Towing eye block	-	-	-	-		